### **PORTWEST PRODUCT SPECIFICATION & TECHNICAL DATA**

#### **AF22 - Araflame Coverall**

**Collection:** Araflame Plus<sup>™</sup> Range: Flame Resistant Shell Fabric: Araflame Plus<sup>™</sup> 200g Box Quantity: 18

#### **Product information**

This winning style has a host of functional features including reflective tape for extra visibility. Triple stitching throughout adds to the strength and durability of AF22. Certified to several EN standards optimal protection is provided for the wearer.

#### **Standards**

EN 1149 -5 ASTM F1959/F1959M-12 (ATPV 8.5 CAL/CM2 (HAF 70.5%)) EN ISO 11612 (A1+A2,B1,C1,F1) EN ISO 11611 Class 1 (A1+A2)



EN 150 11612

٠



#### Araflame Plus<sup>™</sup>

Araflame<sup>™</sup> is an inherently permanent flame resistant aramid. It is extremely flame resistant, lightweight, offers high tensile strength and full anti static protection.

#### **Flame Resistant**

This industry leading range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

#### **Features**

- CE certified
- Inherent flame resistant qualities will not diminish with washing
- · Protection against radiant, convective and contact heat
- Class 1 welding protection
- Flame resistant industrial wash tape
- Triple-stitched seams for extra durability
- · Radio loops for easy clipping of a radio
- Hook and loop cuffs for a secure fit
- Two tier knee pad pockets allowing two positioning options
- 50+ UPF rated fabric to block 98% of UV rays



#### **Available colours**

	Short	Reg	Tall	XTall
Orange		M - 3XL		

# **PORTWEST**.

**PRODUCT SPECIFICATION & TECHNICAL DATA** 

### AF22 - Araflame Coverall Commodity Code: 6211331000

**Test House** 

# Wash care $\bowtie$ $\bigtriangleup$ $\bigcirc$ $\supseteq$ $\bigcirc$ $\bigcirc$

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m <sup>3</sup> )	EAN13	DUN14
AF22ORRM	Orange	65.0	40.0	36.0	0.9400	0.0936	5036108188796	15036108675781
AF22ORRL	Orange	65.0	40.0	36.0	0.9600	0.0936	5036108188789	15036108675774
AF22ORRXL	Orange	65.0	40.0	36.0	1.0000	0.0936	5036108188819	15036108675804
AF22ORRXXL	Orange	65.0	40.0	36.0	1.0400	0.0936	5036108188826	15036108675811
AF22ORRXXXL	Orange	65.0	40.0	36.0	1.0600	0.0936	5036108188833	15036108675828